

Product Code

COO-UV30

3.3

3 ply PVC Abrasion Resistant (4.2mm)

Top Cover [mm]	1mm PVC (Green)
Bottom Cover [mm]	Clear Polyester Monofilament Fabric
Belt Support	Steel - Stainless Steel/Live Rollers
No of Plies	3 ply
Temp Range [°C]	-5 + 80
Max Working Tension [N/mm]	30N/mm 18N/mm for 1% Elongation
Max Width [mm]	2000
Thickness [mm] Nominal	4.2
Normal flexing [mm]	150
Back flexing [mm]	180
Weight [Kg per square meters]	5.4
Join Type	Finger-Overlap-Finger/Bias Lap/Mechanical Fasteners

Applications

- General purpose applications where high resistance abrasions and cutting are required

Distinguishing Qualities

- Moderate resistance to animal fats, vegetable and mineral oils
- Rigid monofilament Polyester fabrics provides good belt stability and resistance to belt curl on the edges
- Top covers of 11mm Green PVC offers excellent service life in a variety of general purpose conveying applications
- Cleated profile can be fitted to the top surface 25, 50 or 75mm high
- Vee rib profiles can be fitted to the bottom surface for improved belt tracking



1300 747 470

www.powergrip.com.au

VIC: 03 9890 0344

NSW: 02 9676 3066

QLD: 07 3275 1717

WA: 08 9456 1122